



POINT REPAIR CARRIERS

EXPANDED LINE FOR MORE VERSATILITY

Features:

- Reduced deflated diameters
- New expanded multi-size line covers pipe sizes from 4"–36" diameters and lengths up to 15' (Custom lengths available)
- Maximum pipe contact guides and center line ensure proper placement of repair medium to minimize waste and increase productivity
- 1/4" NPT Inflation Port with male quick disconnect for ease of connection
- Durable, flexible natural corded rubber
- Bypass design allows sewage bypass during repair – no need to shut down the line
- The flexible design allows all units to be folded in half for transport
- Redesigned integrated caster wheel assembly and bypass channel have been optimized for ease of movement and enhanced bypass of effluent



**TEST
YOUR
BEST**

Part Number	For Pipe Size / Diameter	Length	Inflation Pressure	Bypass Diameter	Weight (lbs.)	Deflated Diameter			Contact Length	
						Plug Diameter	Inside Wheel	Outside Wheel	Maximum	Minimum
279058	4" - 6"	5'	45 psi	NA	10	2.65"	NA	NA	53"	47"
279108	4" - 6"	10'	45 psi	NA	13.5	2.65"	NA	NA	113"	107"
279158	4" - 6"	15'	45 psi	NA	17.5	2.65"	NA	NA	173"	167"
287058	8" - 12"	5'	25 psi	2"	22	4.75"	5.14"	5.6"	48"	42"
287108	8" - 12"	10'	25 psi	2"	30	4.75"	5.14"	5.6"	108"	102"
287158	8" - 12"	15'	25 psi	2"	37.5	4.75"	5.14"	5.6"	168"	162"
288058	12" - 16"	5'	15 psi	2"	25	8.56"	10"	11.9"	50"	45"
288108	12" - 16"	10'	15 psi	2"	35	8.56"	10"	11.9"	110"	105"
288158	12" - 16"	15'	15 psi	2"	45	8.56"	10"	11.9"	170"	165"
289058	18" - 24"	5'	15 psi	2"	74	14.68"	15.42"	17.9"	49"	43"
289108	18" - 24"	10'	15 psi	2"	84	14.68"	15.42"	17.9"	109"	103"
289158	18" - 24"	15'	15 psi	2"	94	14.68"	15.42"	17.9"	169"	163"
284058	24" - 36"	5'	15 psi	4"	107	19.05"	19.56"	22.3"	48"	33"
284108	24" - 36"	10'	15 psi	4"	140.5	19.05"	19.56"	22.3"	108"	93"
284158	24" - 36"	15'	15 psi	4"	182	19.05"	19.56"	22.3"	168"	153"

Custom sizes available - consult the factory.

Call your Oatey Sales Representative for more information.



Find us on

©2017 OateySCS. All Rights Reserved. This information is based on data believed to be reliable but Oatey makes no warranties, express or implied, as to its accuracy and assumes no liability arising out of its use. The data listed falls within the normal range of product properties but should not be used to establish specification limits or used alone as the basis of design. Oatey's liability to purchasers is expressly limited to the terms and conditions of sale. Oatey is a trademark of Oatey Co. Oatey Co. is part of the Oatey family of companies. All other trademarks can be found on www.oatey.com.