



# Burnley Korean Oatey

Version No: 1.2

Safety Data Sheet according to WHMIS 2015 requirements

Issue Date: 04/05/2021

Print Date: 04/05/2021

S.GHS.CAN.EN

## SECTION 1 Identification

### Product Identifier

Product name	Burnley Korean
Synonyms	Not Available
Proper shipping name	CORROSIVE SOLID, N.O.S. (contains zinc chloride)
Other means of identification	Not available.

### Recommended use of the chemical and restrictions on use

Relevant identified uses	Soldering paste
--------------------------	-----------------

### Name, address, and telephone number of the chemical manufacturer, importer, or other responsible party

Registered company name	Oatey
Address	620 Steven Ct #11, Newmarket, ON L3Y 6Z2 Canada
Telephone	905-898-2557
Fax	Not Available
Website	Not Available
Email	info@oatey.com

### Emergency phone number

Association / Organisation	ChemTrec
Emergency telephone numbers	1-800-424-9300 (Outside the US 1-703-527-3887)
Other emergency telephone numbers	Emergency First Aid: 1-877-740-5015

## SECTION 2 Hazard(s) identification

### Classification of the substance or mixture

Classification	Skin Corrosion/Irritation Category 1B, Corrosive to Metals Category 1, Serious Eye Damage/Eye Irritation Category 1, Acute Toxicity (Oral) Category 4, Physical hazards not otherwise classified Category 1
----------------	---

### Label elements

Hazard pictogram(s)	
---------------------	--

Signal word	Danger
-------------	--------

### Hazard statement(s)

## Burnley Korean

H314	Causes severe skin burns and eye damage.
H290	May be corrosive to metals.
H302	Harmful if swallowed.

**Physical and Health hazard(s) not otherwise classified**

Toxic fumes may be released during a fire.

**Precautionary statement(s) Prevention**

P260	Do not breathe mist/vapours/spray.
P264	Wash thoroughly after handling.
P280	Wear protective gloves/protective clothing/eye protection/face protection.
P234	Keep only in original packaging.
P270	Do not eat, drink or smoke when using this product.

**Precautionary statement(s) Response**

P301+P330+P331	IF SWALLOWED: Rinse mouth. Do NOT induce vomiting.
P303+P361+P353	IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water [or shower].
P305+P351+P338	IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
P310	Immediately call a POISON CENTER/doctor/physician/first aider.
P321	Specific treatment (see on this label)
P330	Rinse mouth.
P363	Wash contaminated clothing before reuse.
P390	Absorb spillage to prevent material damage.
P301+P312	IF SWALLOWED: Call a POISON CENTER/doctor/physician/first aider/if you feel unwell.
P304+P340	IF INHALED: Remove person to fresh air and keep comfortable for breathing.

**Precautionary statement(s) Storage**

P405	Store locked up.
P406	Store in a corrosion resistant container with a resistant inner liner.

**Precautionary statement(s) Disposal**

P501	Dispose of contents/container to authorised hazardous or special waste collection point in accordance with any local regulation.
------	--

**SECTION 3 Composition / information on ingredients****Substances**

See section below for composition of Mixtures

**Mixtures**

CAS No	%[weight]	Name
8009-03-8.	45-70	<u>petrolatum</u>
7646-85-7	20-30	<u>zinc chloride</u>

**SECTION 4 First-aid measures****Description of first aid measures**

<b>Eye Contact</b>	<p>If this product comes in contact with the eyes:</p> <ul style="list-style-type: none"> <li>▶ Immediately hold eyelids apart and flush the eye continuously with running water.</li> <li>▶ Ensure complete irrigation of the eye by keeping eyelids apart and away from eye and moving the eyelids by occasionally lifting the upper and lower lids.</li> <li>▶ Continue flushing until advised to stop by the Poisons Information Centre or a doctor, or for at least 15 minutes.</li> <li>▶ Transport to hospital or doctor without delay.</li> <li>▶ Removal of contact lenses after an eye injury should only be undertaken by skilled personnel.</li> </ul>
--------------------	--

## Burnley Korean

<b>Skin Contact</b>	<p>If skin or hair contact occurs:</p> <ul style="list-style-type: none"> <li>▶ Immediately flush body and clothes with large amounts of water, using safety shower if available.</li> <li>▶ Quickly remove all contaminated clothing, including footwear.</li> <li>▶ Wash skin and hair with running water. Continue flushing with water until advised to stop by the Poisons Information Centre.</li> <li>▶ Transport to hospital, or doctor.</li> </ul> <p>In case of burns:</p> <ul style="list-style-type: none"> <li>▶ Immediately apply cold water to burn either by immersion or wrapping with saturated clean cloth.</li> <li>▶ <b>DO NOT</b> remove or cut away clothing over burnt areas. <b>DO NOT</b> pull away clothing which has adhered to the skin as this can cause further injury.</li> <li>▶ <b>DO NOT</b> break blister or remove solidified material.</li> <li>▶ Quickly cover wound with dressing or clean cloth to help prevent infection and to ease pain.</li> <li>▶ For large burns, sheets, towels or pillow slips are ideal; leave holes for eyes, nose and mouth.</li> <li>▶ <b>DO NOT</b> apply ointments, oils, butter, etc. to a burn under any circumstances.</li> <li>▶ Water may be given in small quantities if the person is conscious.</li> <li>▶ Alcohol is not to be given under any circumstances.</li> <li>▶ Reassure.</li> <li>▶ Treat for shock by keeping the person warm and in a lying position.</li> <li>▶ Seek medical aid and advise medical personnel in advance of the cause and extent of the injury and the estimated time of arrival of the patient.</li> </ul>
<b>Inhalation</b>	<ul style="list-style-type: none"> <li>▶ If fumes or combustion products are inhaled remove from contaminated area.</li> <li>▶ Lay patient down. Keep warm and rested.</li> <li>▶ Prostheses such as false teeth, which may block airway, should be removed, where possible, prior to initiating first aid procedures.</li> <li>▶ Apply artificial respiration if not breathing, preferably with a demand valve resuscitator, bag-valve mask device, or pocket mask as trained. Perform CPR if necessary.</li> <li>▶ Transport to hospital, or doctor, without delay.</li> <li>▶ Inhalation of vapours or aerosols (mists, fumes) may cause lung oedema.</li> <li>▶ Corrosive substances may cause lung damage (e.g. lung oedema, fluid in the lungs).</li> <li>▶ As this reaction may be delayed up to 24 hours after exposure, affected individuals need complete rest (preferably in semi-recumbent posture) and must be kept under medical observation even if no symptoms are (yet) manifested.</li> <li>▶ Before any such manifestation, the administration of a spray containing a dexamethasone derivative or beclomethasone derivative may be considered.</li> </ul> <p><b>This must definitely be left to a doctor or person authorised by him/her.</b> (ICSC13719)</p>
<b>Ingestion</b>	<ul style="list-style-type: none"> <li>▶ For advice, contact a Poisons Information Centre or a doctor at once.</li> <li>▶ Urgent hospital treatment is likely to be needed.</li> <li>▶ If swallowed do <b>NOT</b> induce vomiting.</li> <li>▶ If vomiting occurs, lean patient forward or place on left side (head-down position, if possible) to maintain open airway and prevent aspiration.</li> <li>▶ Observe the patient carefully.</li> <li>▶ Never give liquid to a person showing signs of being sleepy or with reduced awareness; i.e. becoming unconscious.</li> <li>▶ Give water to rinse out mouth, then provide liquid slowly and as much as casualty can comfortably drink.</li> <li>▶ Transport to hospital or doctor without delay.</li> </ul>

**Indication of any immediate medical attention and special treatment needed**

Treat symptomatically.

- ▶ Heavy and persistent skin contamination over many years may lead to dysplastic changes. Pre-existing skin disorders may be aggravated by exposure to this product.
- ▶ In general, emesis induction is unnecessary with high viscosity, low volatility products, i.e. most oils and greases.
- ▶ High pressure accidental injection through the skin should be assessed for possible incision, irrigation and/or debridement.

**NOTE:** Injuries may not seem serious at first, but within a few hours tissue may become swollen, discoloured and extremely painful with extensive subcutaneous necrosis. Product may be forced through considerable distances along tissue planes.

For acute or short term repeated exposures to strong acids:

- ▶ Airway problems may arise from laryngeal edema and inhalation exposure. Treat with 100% oxygen initially.
- ▶ Respiratory distress may require cricothyroidotomy if endotracheal intubation is contraindicated by excessive swelling
- ▶ Intravenous lines should be established immediately in all cases where there is evidence of circulatory compromise.
- ▶ Strong acids produce a coagulation necrosis characterised by formation of a coagulum (eschar) as a result of the desiccating action of the acid on proteins in specific tissues.

**INGESTION:**

- ▶ Immediate dilution (milk or water) within 30 minutes post ingestion is recommended.
- ▶ **DO NOT** attempt to neutralise the acid since exothermic reaction may extend the corrosive injury.
- ▶ Be careful to avoid further vomit since re-exposure of the mucosa to the acid is harmful. Limit fluids to one or two glasses in an adult.
- ▶ Charcoal has no place in acid management.
- ▶ Some authors suggest the use of lavage within 1 hour of ingestion.

**SKIN:**

- ▶ Skin lesions require copious saline irrigation. Treat chemical burns as thermal burns with non-adherent gauze and wrapping.
- ▶ Deep second-degree burns may benefit from topical silver sulfadiazine.

**EYE:**

- ▶ Eye injuries require retraction of the eyelids to ensure thorough irrigation of the conjunctival cul-de-sacs. Irrigation should last at least 20-30 minutes. **DO**

Continued...

## Burnley Korean

**NOT** use neutralising agents or any other additives. Several litres of saline are required.

- ▶ Cycloplegic drops, (1% cyclopentolate for short-term use or 5% homatropine for longer term use) antibiotic drops, vasoconstrictive agents or artificial tears may be indicated dependent on the severity of the injury.
- ▶ Steroid eye drops should only be administered with the approval of a consulting ophthalmologist).

[Ellenhorn and Barceloux: Medical Toxicology]

### SECTION 5 Fire-fighting measures

#### Extinguishing media

Use of carbon tetrachloride to extinguish a wax fire produced an explosion. It is postulated that to a violent reaction between unsaturated wax components and carbon tetrachloride initiated by free radicals from decomposing peroxides might have occurred; alternately contact of cold water with the molten material might have lead to a vapour explosion.

- ▶ Do NOT direct a solid stream of water or foam into burning molten material; this may cause spattering and spread the fire.
- ▶ Foam.
- ▶ Dry chemical powder.
- ▶ BCF (where regulations permit).
- ▶ Carbon dioxide.
- ▶ Water spray or fog - Large fires only.

#### Special hazards arising from the substrate or mixture

<b>Fire Incompatibility</b>	▶ Avoid contamination with oxidising agents i.e. nitrates, oxidising acids, chlorine bleaches, pool chlorine etc. as ignition may result
-----------------------------	--

#### Special protective equipment and precautions for fire-fighters

<b>Fire Fighting</b>	<ul style="list-style-type: none"> <li>▶ Alert Fire Brigade and tell them location and nature of hazard.</li> <li>▶ Wear full body protective clothing with breathing apparatus.</li> <li>▶ Prevent, by any means available, spillage from entering drains or water course.</li> <li>▶ Use fire fighting procedures suitable for surrounding area.</li> <li>▶ <b>Do not</b> approach containers suspected to be hot.</li> <li>▶ Cool fire exposed containers with water spray from a protected location.</li> <li>▶ If safe to do so, remove containers from path of fire.</li> <li>▶ Equipment should be thoroughly decontaminated after use.</li> </ul>
<b>Fire/Explosion Hazard</b>	<ul style="list-style-type: none"> <li>▶ Combustible.</li> <li>▶ Slight fire hazard when exposed to heat or flame.</li> <li>▶ Acids may react with metals to produce hydrogen, a highly flammable and explosive gas.</li> <li>▶ Heating may cause expansion or decomposition leading to violent rupture of containers.</li> <li>▶ May emit acrid smoke and corrosive fumes.</li> </ul> <p>Combustion products include: carbon monoxide (CO) carbon dioxide (CO<sub>2</sub>) hydrogen chloride phosgene metal oxides other pyrolysis products typical of burning organic material.</p> <p><b>NOTE:</b> Burns with intense heat. Produces melting, flowing, burning liquid and dense acrid black smoke. <b>CARE:</b> Water in contact with hot liquid may cause foaming and a steam explosion with wide scattering of hot oil and possible severe burns. Foaming may cause overflow of containers and may result in possible fire.</p>

### SECTION 6 Accidental release measures

#### Personal precautions, protective equipment and emergency procedures

See section 8

#### Environmental precautions

See section 12

#### Methods and material for containment and cleaning up

<b>Minor Spills</b>	<ul style="list-style-type: none"> <li>▶ Remove all ignition sources.</li> <li>▶ Clean up all spills immediately.</li> <li>▶ Avoid contact with skin and eyes.</li> <li>▶ Control personal contact with the substance, by using protective equipment.</li> <li>▶ Use dry clean up procedures and avoid generating dust.</li> </ul>
---------------------	--

Continued...

## Burnley Korean

	<ul style="list-style-type: none"> <li>▶ Place in a suitable, labelled container for waste disposal.</li> <li>▶ Drains for storage or use areas should have retention basins for pH adjustments and dilution of spills before discharge or disposal of material.</li> <li>▶ Check regularly for spills and leaks.</li> </ul>
<b>Major Spills</b>	<ul style="list-style-type: none"> <li>▶ Clear area of personnel and move upwind.</li> <li>▶ Alert Fire Brigade and tell them location and nature of hazard.</li> <li>▶ Wear full body protective clothing with breathing apparatus.</li> <li>▶ Prevent, by any means available, spillage from entering drains or water course.</li> <li>▶ Consider evacuation (or protect in place).</li> <li>▶ Stop leak if safe to do so.</li> <li>▶ Contain spill with sand, earth or vermiculite.</li> <li>▶ Collect recoverable product into labelled containers for recycling.</li> <li>▶ Neutralise/decontaminate residue (see Section 13 for specific agent).</li> <li>▶ Collect solid residues and seal in labelled drums for disposal.</li> <li>▶ Wash area and prevent runoff into drains.</li> <li>▶ After clean up operations, decontaminate and launder all protective clothing and equipment before storing and re-using.</li> <li>▶ If contamination of drains or waterways occurs, advise emergency services.</li> </ul>

Personal Protective Equipment advice is contained in Section 8 of the SDS.

## SECTION 7 Handling and storage

### Precautions for safe handling

<b>Safe handling</b>	<ul style="list-style-type: none"> <li>▶ The greatest potential for injury caused by molten materials occurs during purging of machinery (moulders, extruders etc.)</li> <li>▶ It is essential that workers in the immediate area of the machinery wear eye and skin protection (such as full face, safety glasses, heat resistant gloves, overalls and safety boots) as protection from thermal burns.</li> <li>▶ Fumes or vapours emitted from hot melted materials, during converting operations, may condense on overhead metal surfaces or exhaust ducts. The condensate may contain substances which are irritating or toxic. Avoid contact of that material with the skin. Wear rubber or other impermeable gloves when cleaning contaminated areas.</li> <li>▶ Avoid process temperatures above decomposition temperatures. Overheating may occur at excessively high cylinder heats, overworking of the melt by wrong screw configuration, or by long dwell time in the machine. Under such conditions, thermal emissions and heat-degradation products might, without proper ventilation, reach hazardous concentrations in the converting area. Hot purgings should be collected only as thin flat strands to allow for rapid cooling. Hot purgings should be cooled by quenching in water in a well-ventilated area.</li> <li>▶ Electrostatic discharge may be generated during pumping - this may result in fire.</li> <li>▶ Ensure electrical continuity by bonding and grounding (earthing) all equipment.</li> <li>▶ Restrict line velocity during pumping in order to avoid generation of electrostatic discharge (<math>\leq 1</math> m/sec until fill pipe submerged to twice its diameter, then <math>\leq 7</math> m/sec).</li> <li>▶ Avoid splash filling.</li> <li>▶ Do NOT use compressed air for filling discharging or handling operations.</li> <li>▶ Avoid all personal contact, including inhalation.</li> <li>▶ Wear protective clothing when risk of exposure occurs.</li> <li>▶ Use in a well-ventilated area.</li> <li>▶ Avoid contact with moisture.</li> <li>▶ Avoid contact with incompatible materials.</li> <li>▶ When handling, <b>DO NOT</b> eat, drink or smoke.</li> <li>▶ Keep containers securely sealed when not in use.</li> <li>▶ Avoid physical damage to containers.</li> <li>▶ Always wash hands with soap and water after handling.</li> <li>▶ Work clothes should be laundered separately. Launder contaminated clothing before re-use.</li> <li>▶ Use good occupational work practice.</li> <li>▶ Observe manufacturer's storage and handling recommendations contained within this SDS.</li> <li>▶ Atmosphere should be regularly checked against established exposure standards to ensure safe working conditions are maintained.</li> </ul>
<b>Other information</b>	<ul style="list-style-type: none"> <li>▶ Store in original containers.</li> <li>▶ Keep containers securely sealed.</li> <li>▶ Store in a cool, dry, well-ventilated area.</li> <li>▶ Store away from incompatible materials and foodstuff containers.</li> <li>▶ Protect containers against physical damage and check regularly for leaks.</li> <li>▶ Observe manufacturer's storage and handling recommendations contained within this SDS.</li> </ul>

### Conditions for safe storage, including any incompatibilities

<b>Suitable container</b>	<ul style="list-style-type: none"> <li>▶ <b>DO NOT</b> use aluminium or galvanised containers</li> <li>▶ Check regularly for spills and leaks</li> </ul>
---------------------------	--

## Burnley Korean

	<ul style="list-style-type: none"> <li>▶ Lined metal can, lined metal pail/ can.</li> <li>▶ Plastic pail.</li> <li>▶ Polyliner drum.</li> <li>▶ Packing as recommended by manufacturer.</li> <li>▶ Check all containers are clearly labelled and free from leaks.</li> </ul> <p>For low viscosity materials</p> <ul style="list-style-type: none"> <li>▶ Drums and jerricans must be of the non-removable head type.</li> <li>▶ Where a can is to be used as an inner package, the can must have a screwed enclosure.</li> </ul> <p>For materials with a viscosity of at least 2680 cSt. (23 deg. C) and solids (between 15 C deg. and 40 deg C.):</p> <ul style="list-style-type: none"> <li>▶ Removable head packaging;</li> <li>▶ Cans with friction closures and</li> <li>▶ low pressure tubes and cartridges</li> </ul> <p>may be used.</p> <p>-</p> <p>Where combination packages are used, and the inner packages are of glass, porcelain or stoneware, there must be sufficient inert cushioning material in contact with inner and outer packages unless the outer packaging is a close fitting moulded plastic box and the substances are not incompatible with the plastic.</p>
<b>Storage incompatibility</b>	<p>Zinc chloride:</p> <ul style="list-style-type: none"> <li>▶ reacts with water forming an acidic solution (pH about 4); zinc oxychloride may be formed with large amounts of water</li> <li>▶ reacts violently with strong bases, potassium</li> <li>▶ attacks metals as fume or in the presence of moisture.</li> <li>▶ Inorganic acids are generally soluble in water with the release of hydrogen ions. The resulting solutions have pH's of less than 7.0.</li> <li>▶ Inorganic acids neutralise chemical bases (for example: amines and inorganic hydroxides) to form salts - neutralisation can generate dangerously large amounts of heat in small spaces.</li> <li>▶ The dissolution of inorganic acids in water or the dilution of their concentrated solutions with additional water may generate significant heat.</li> <li>▶ The addition of water to inorganic acids often generates sufficient heat in the small region of mixing to cause some of the water to boil explosively. The resulting 'bumping' can spatter the acid.</li> <li>▶ Inorganic acids react with active metals, including such structural metals as aluminum and iron, to release hydrogen, a flammable gas.</li> <li>▶ Inorganic acids can initiate the polymerisation of certain classes of organic compounds.</li> <li>▶ Inorganic acids react with cyanide compounds to release gaseous hydrogen cyanide.</li> <li>▶ Inorganic acids generate flammable and/or toxic gases in contact with dithiocarbamates, isocyanates, mercaptans, nitrides, nitriles, sulfides, and strong reducing agents. Additional gas-generating reactions occur with sulfites, nitrites, thiosulfates (to give H<sub>2</sub>S and SO<sub>3</sub>), dithionites (SO<sub>2</sub>), and even carbonates.</li> <li>▶ Acids often catalyse (increase the rate of) chemical reactions.</li> <li>▶ <b>WARNING:</b> Avoid or control reaction with peroxides. All <i>transition metal</i> peroxides should be considered as potentially explosive. For example transition metal complexes of alkyl hydroperoxides may decompose explosively.</li> <li>▶ The pi-complexes formed between chromium(0), vanadium(0) and other transition metals (haloarene-metal complexes) and mono-or poly-fluorobenzene show extreme sensitivity to heat and are explosive.</li> <li>▶ Avoid reaction with borohydrides or cyanoborohydrides</li> </ul> <p><b>CARE:</b> Water in contact with heated material may cause foaming or a steam explosion with possible severe burns from wide scattering of hot material. Resultant overflow of containers may result in fire.</p> <ul style="list-style-type: none"> <li>▶ Segregate from alkalis, oxidising agents and chemicals readily decomposed by acids, i.e. cyanides, sulfides, carbonates.</li> <li>▶ Reacts with mild steel, galvanised steel / zinc producing hydrogen gas which may form an explosive mixture with air.</li> </ul>

**SECTION 8 Exposure controls / personal protection****Control parameters****Occupational Exposure Limits (OEL)****INGREDIENT DATA**

Source	Ingredient	Material name	TWA	STEL	Peak	Notes
Canada - Yukon Permissible Concentrations for Airborne Contaminant Substances	petrolatum	Oil mist, mineral	5 mg/m <sup>3</sup>	10 mg/m <sup>3</sup>	Not Available	Not Available
Canada - Nova Scotia Occupational Exposure Limits	petrolatum	Oil mist - mineral	5 mg/m <sup>3</sup>	10 mg/m <sup>3</sup>	Not Available	TLV Basis: lung. As sampled by method that does not collect vapor.
Canada - Alberta Occupational Exposure Limits	petrolatum	Oil mist, mineral	5 mg/m <sup>3</sup>	10 mg/m <sup>3</sup>	Not Available	Not Available
Canada - Saskatchewan Occupational Health and Safety Regulations -	petrolatum	Oil mist, mineral	5 mg/m <sup>3</sup>	10 mg/m <sup>3</sup>	Not Available	Not Available

Continued...

## Burnley Korean

Source	Ingredient	Material name	TWA	STEL	Peak	Notes
Contamination Limits						
Canada - Manitoba Occupational Exposure Limits	petrolatum	Not Available	Not Available	Not Available	Not Available	TLV® Basis: URT irr
Canada - Manitoba Occupational Exposure Limits	petrolatum	Not Available	5 mg/m3	Not Available	Not Available	TLV® Basis: URT irr
Canada - British Columbia Occupational Exposure Limits	petrolatum	Oil mist - mineral, mildly refined	0.2 mg/m3	Not Available	Not Available	Not Available
Canada - British Columbia Occupational Exposure Limits	petrolatum	Oil mist - mineral, severely refined	1 mg/m3	Not Available	Not Available	Not Available
Canada - Prince Edward Island Occupational Exposure Limits	petrolatum	Mineral oil, excluding metal working fluids - Poorly and mildly refined	Not Available	Not Available	Not Available	TLV® Basis: URT irr
Canada - Prince Edward Island Occupational Exposure Limits	petrolatum	Mineral oil, excluding metal working fluids - Pure, highly and severely refined	5 mg/m3	Not Available	Not Available	TLV® Basis: URT irr
Canada - Northwest Territories Occupational Exposure Limits	petrolatum	Oil mist, mineral	5 mg/m3	10 mg/m3	Not Available	Not Available
Canada - Quebec Permissible Exposure Values for Airborne Contaminants	petrolatum	Mineral oil (mist)	5 mg/m3	10 mg/m3	Not Available	Not Available
Canada - Yukon Permissible Concentrations for Airborne Contaminant Substances	zinc chloride	Zinc chloride fume	1 mg/m3	2 mg/m3	Not Available	Not Available
Canada - Nova Scotia Occupational Exposure Limits	zinc chloride	Zinc chloride - Fume	1 mg/m3	2 mg/m3	Not Available	TLV Basis: lower & upper respiratory tract irritation
Canada - Alberta Occupational Exposure Limits	zinc chloride	Zinc chloride fume	1 mg/m3	2 mg/m3	Not Available	Not Available
Canada - Saskatchewan Occupational Health and Safety Regulations - Contamination Limits	zinc chloride	Zinc chloride fume	1 mg/m3	2 mg/m3	Not Available	Not Available
Canada - Manitoba Occupational Exposure Limits	zinc chloride	Not Available	1 mg/m3	2 mg/m3	Not Available	TLV® Basis: LRT & URT irr
Canada - British Columbia Occupational Exposure Limits	zinc chloride	Zinc chloride - Fume	1 mg/m3	2 mg/m3	Not Available	Not Available
Canada - Prince Edward Island Occupational Exposure Limits	zinc chloride	Zinc chloride fume	1 mg/m3	2 mg/m3	Not Available	TLV® Basis: LRT & URT irr
Canada - Northwest Territories Occupational Exposure Limits	zinc chloride	Zinc chloride fume	1 mg/m3	2 mg/m3	Not Available	Not Available
Canada - Quebec Permissible Exposure Values for Airborne Contaminants	zinc chloride	Zinc chloride, fume	1 mg/m3	Not Available	Not Available	Not Available

## Exposure controls

<b>Appropriate engineering controls</b>	<p>Engineering controls are used to remove a hazard or place a barrier between the worker and the hazard. Well-designed engineering controls can be highly effective in protecting workers and will typically be independent of worker interactions to provide this high level of protection.</p> <p>The basic types of engineering controls are:</p> <p>Process controls which involve changing the way a job activity or process is done to reduce the risk.</p> <p>Enclosure and/or isolation of emission source which keeps a selected hazard 'physically' away from the worker and ventilation that strategically 'adds' and 'removes' air in the work environment. Ventilation can remove or dilute an air contaminant if designed properly. The design of a ventilation system must match the particular process and chemical or contaminant in use.</p>
---	---

Continued...

## Burnley Korean

Employers may need to use multiple types of controls to prevent employee overexposure.

Local exhaust ventilation usually required. If risk of overexposure exists, wear approved respirator. Correct fit is essential to obtain adequate protection. Supplied-air type respirator may be required in special circumstances. Correct fit is essential to ensure adequate protection.

An approved self contained breathing apparatus (SCBA) may be required in some situations.

Provide adequate ventilation in warehouse or closed storage area. Air contaminants generated in the workplace possess varying 'escape' velocities which, in turn, determine the 'capture velocities' of fresh circulating air required to effectively remove the contaminant.

Type of Contaminant:	Air Speed:
solvent, vapours, degreasing etc., evaporating from tank (in still air).	0.25-0.5 m/s (50-100 f/min.)
aerosols, fumes from pouring operations, intermittent container filling, low speed conveyer transfers, welding, spray drift, plating acid fumes, pickling (released at low velocity into zone of active generation)	0.5-1 m/s (100-200 f/min.)
direct spray, spray painting in shallow booths, drum filling, conveyer loading, crusher dusts, gas discharge (active generation into zone of rapid air motion)	1-2.5 m/s (200-500 f/min.)
grinding, abrasive blasting, tumbling, high speed wheel generated dusts (released at high initial velocity into zone of very high rapid air motion).	2.5-10 m/s (500-2000 f/min.)

Within each range the appropriate value depends on:

Lower end of the range	Upper end of the range
1: Room air currents minimal or favourable to capture	1: Disturbing room air currents
2: Contaminants of low toxicity or of nuisance value only.	2: Contaminants of high toxicity
3: Intermittent, low production.	3: High production, heavy use
4: Large hood or large air mass in motion	4: Small hood-local control only

Simple theory shows that air velocity falls rapidly with distance away from the opening of a simple extraction pipe. Velocity generally decreases with the square of distance from the extraction point (in simple cases). Therefore the air speed at the extraction point should be adjusted, accordingly, after reference to distance from the contaminating source. The air velocity at the extraction fan, for example, should be a minimum of 1-2 m/s (200-400 f/min) for extraction of solvents generated in a tank 2 meters distant from the extraction point. Other mechanical considerations, producing performance deficits within the extraction apparatus, make it essential that theoretical air velocities are multiplied by factors of 10 or more when extraction systems are installed or used.

For molten materials:

Provide mechanical ventilation; in general such ventilation should be provided at compounding/ converting areas and at fabricating/ filling work stations where the material is heated. Local exhaust ventilation should be used over and in the vicinity of machinery involved in handling the molten material.

Keep dry!!

Processing temperatures may be well above boiling point of water, so wet or damp material may cause a serious steam explosion if used in unvented equipment.

## Personal protection



## Eye and face protection

- ▶ Chemical goggles.
- ▶ Full face shield may be required for supplementary but never for primary protection of eyes.
- ▶ Contact lenses may pose a special hazard; soft contact lenses may absorb and concentrate irritants. A written policy document, describing the wearing of lenses or restrictions on use, should be created for each workplace or task. This should include a review of lens absorption and adsorption for the class of chemicals in use and an account of injury experience. Medical and first-aid personnel should be trained in their removal and suitable equipment should be readily available. In the event of chemical exposure, begin eye irrigation immediately and remove contact lens as soon as practicable. Lens should be removed at the first signs of eye redness or irritation - lens should be removed in a clean environment only after workers have washed hands thoroughly. [CDC NIOSH Current Intelligence Bulletin 59], [AS/NZS 1336 or national equivalent]

## Skin protection

See Hand protection below

## Hands/feet protection

- ▶ Wear chemical protective gloves, e.g. PVC.
- ▶ Wear safety footwear or safety gumboots, e.g. Rubber
- ▶ When handling hot materials wear heat resistant, elbow length gloves.
- ▶ Rubber gloves are not recommended when handling hot objects, materials
- ▶ Protective gloves eg. Leather gloves or gloves with Leather facing

## Body protection

See Other protection below

## Other protection

- ▶ When handling hot or molten liquids, wear trousers or overalls outside of boots, to avoid spills entering boots.
- ▶ Usually handled as molten liquid which requires worker thermal protection and increases hazard of vapour exposure.
- ▶ **CAUTION:** Vapours may be irritating.

Continued...



## Burnley Korean

- ▶ Overalls.
- ▶ PVC Apron.
- ▶ PVC protective suit may be required if exposure severe.
- ▶ Eyewash unit.
- ▶ Ensure there is ready access to a safety shower.

**Respiratory protection**

Type AB-P Filter of sufficient capacity. (AS/NZS 1716 & 1715, EN 143:2000 & 149:2001, ANSI Z88 or national equivalent)

**SECTION 9 Physical and chemical properties****Information on basic physical and chemical properties**

<b>Appearance</b>	Reddish brown paste		
<b>Physical state</b>	Paste	<b>Relative density (Agua= 1)</b>	0.87
<b>Odour</b>	Not Available	<b>Partition coefficient n-octanol / water</b>	Not Available
<b>Odour threshold</b>	Not Available	<b>Auto-ignition temperature (°C)</b>	Not Available
<b>pH (as supplied)</b>	Not Available	<b>Decomposition temperature</b>	Not Available
<b>Melting point / freezing point (°C)</b>	37.8	<b>Viscosity (cSt)</b>	Not Available
<b>Initial boiling point and boiling range (°C)</b>	Not Available	<b>Molecular weight (g/mol)</b>	Not Available
<b>Flash point (°C)</b>	182 - 221	<b>Taste</b>	Not Available
<b>Evaporation rate</b>	Not Available	<b>Explosive properties</b>	Not Available
<b>Flammability</b>	Not Applicable	<b>Oxidising properties</b>	Not Available
<b>Upper Explosive Limit (%)</b>	Not Available	<b>Surface Tension (dyn/cm or mN/m)</b>	Not Available
<b>Lower Explosive Limit (%)</b>	Not Available	<b>Volatile Component (%vol)</b>	Not Available
<b>Vapour pressure (kPa)</b>	29.06	<b>Gas group</b>	Not Available
<b>Solubility in water</b>	Partly miscible	<b>pH as a solution (1%)</b>	Not Available
<b>Vapour density (Air = 1)</b>	Not Available	<b>VOC g/L</b>	Not Available

**SECTION 10 Stability and reactivity**

<b>Reactivity</b>	See section 7
<b>Chemical stability</b>	▶ Contact with alkaline material liberates heat
<b>Possibility of hazardous reactions</b>	See section 7
<b>Conditions to avoid</b>	See section 7
<b>Incompatible materials</b>	See section 7
<b>Hazardous decomposition products</b>	See section 5

**SECTION 11 Toxicological information****Information on toxicological effects**

<b>Inhaled</b>	The material can cause respiratory irritation in some persons. The body's response to such irritation can cause further lung damage.
----------------	--

Continued...

## Burnley Korean

	<p>Hydrogen chloride (HCl) vapour or fumes present a hazard from a single acute exposure. Exposures of 1300 to 2000 ppm have been lethal to humans in a few minutes.</p> <p>Inhalation of HCl may cause choking, coughing, burning sensation and may cause ulceration of the nose, throat and larynx. Fluid on the lungs followed by generalised lung damage may follow.</p> <p>Breathing of HCl vapour may aggravate asthma and inflammatory or fibrotic pulmonary disease.</p> <p>High concentrations cause necrosis of the tracheal and bronchial epithelium, pulmonary oedema, atelectasis and emphysema and damage to the pulmonary blood vessels and liver.</p> <p>Corrosive acids can cause irritation of the respiratory tract, with coughing, choking and mucous membrane damage. There may be dizziness, headache, nausea and weakness.</p> <p>Processing for an overly long time or processing at overly high temperatures may cause generation and release of highly irritating vapours, which irritate eyes, nose, throat, causing red itching eyes, coughing, sore throat.</p> <ul style="list-style-type: none"> <li>▶ Usually handled as molten liquid which requires worker thermal protection and increases hazard of vapour exposure.</li> <li>▶ <b>CAUTION:</b> Vapours may be irritating.</li> </ul>
Ingestion	<p>Accidental ingestion of the material may be harmful; animal experiments indicate that ingestion of less than 150 gram may be fatal or may produce serious damage to the health of the individual.</p> <p>The material can produce chemical burns within the oral cavity and gastrointestinal tract following ingestion.</p> <p>The absorption of n-paraffins is inversely proportional to the carbon chain length, with little absorption above C30. N-paraffins may be absorbed to a greater extent than isoparaffins or cycloparaffins.</p> <p>Results of extraction and migration tests that have been performed on waxes and wax-bearing products indicate that hydrocarbon waxes consumed in the diet are unlikely to be absorbed or metabolized in detectable or significant amounts. Hydrocarbon waxes are less likely to be toxic than hydrocarbon oils.</p> <p>Ingestion of acidic corrosives may produce burns around and in the mouth, the throat and oesophagus. Immediate pain and difficulties in swallowing and speaking may also be evident.</p>
Skin Contact	<p>The material can produce chemical burns following direct contact with the skin.</p> <p>Irritation and skin reactions are possible with sensitive skin</p> <p>Skin contact with acidic corrosives may result in pain and burns; these may be deep with distinct edges and may heal slowly with the formation of scar tissue.</p> <p>The liquid may be able to be mixed with fats or oils and may degrease the skin, producing a skin reaction described as non-allergic contact dermatitis. The material is unlikely to produce an irritant dermatitis as described in EC Directives.</p> <p>The material may accentuate any pre-existing dermatitis condition</p> <p>Open cuts, abraded or irritated skin should not be exposed to this material</p> <p>Entry into the blood-stream, through, for example, cuts, abrasions or lesions, may produce systemic injury with harmful effects. Examine the skin prior to the use of the material and ensure that any external damage is suitably protected.</p>
Eye	<p>The material can produce chemical burns to the eye following direct contact. Vapours or mists may be extremely irritating.</p> <p>If applied to the eyes, this material causes severe eye damage.</p> <p>Irritation of the eyes may produce a heavy secretion of tears (lachrymation).</p> <p>Direct eye contact with acid corrosives may produce pain, tears, sensitivity to light and burns. Mild burns of the epithelia generally recover rapidly and completely.</p>
Chronic	<p>Long-term exposure to respiratory irritants may result in airways disease, involving difficulty breathing and related whole-body problems.</p> <p>Substance accumulation, in the human body, may occur and may cause some concern following repeated or long-term occupational exposure.</p> <p>Repeated or prolonged exposure to acids may result in the erosion of teeth, swelling and/or ulceration of mouth lining. Irritation of airways to lung, with cough, and inflammation of lung tissue often occurs.</p> <p>Implantation studies in rats show that paraffin oils may cause tumours. As a general rule, the highly refined paraffins are believed to contain less suspect polyaromatic hydrocarbons than less refined grades or waxes derived from naphthenic base-stocks.</p> <p>Chronic minor exposure to hydrogen chloride (HCl) vapour or fume may cause discolouration or erosion of the teeth, bleeding of the nose and gums; and ulceration of the mucous membranes of the nose. Workers exposed to hydrochloric acid suffered from stomach inflammation and a number of cases of chronic bronchitis (airway inflammation) have also been reported. Repeated or prolonged exposure to dilute solutions of hydrogen chloride may cause skin inflammation.</p> <p>Welding or flame cutting of metals with zinc or zinc dust coatings may result in inhalation of zinc oxide fume; high concentrations of zinc oxide fume may result in 'metal fume fever'; also known as 'brass chills', an industrial disease of short duration. [I.L.O] Symptoms include malaise, fever, weakness, nausea and may appear quickly if operations occur in enclosed or poorly ventilated areas.</p> <p>Oil may contact the skin or be inhaled. Extended exposure can lead to eczema, inflammation of hair follicles, pigmentation of the face and warts on the soles of the feet.</p>

Burnley Korean	TOXICITY	IRRITATION
	Not Available	Not Available

Acute Toxicity	✓	Carcinogenicity	✗
Skin Irritation/Corrosion	✓	Reproductivity	✗

## Burnley Korean

Serious Eye Damage/Irritation	✓	STOT - Single Exposure	✗
Respiratory or Skin sensitisation	✗	STOT - Repeated Exposure	✗
Mutagenicity	✗	Aspiration Hazard	✗

## SECTION 12 Ecological information

## Toxicity

Burnley Korean	Endpoint	Test Duration (hr)	Species	Value	Source
	Not Available	Not Available	Not Available	Not Available	Not Available

petrolatum	Endpoint	Test Duration (hr)	Species	Value	Source
	Not Available	Not Available	Not Available	Not Available	Not Available

zinc chloride	Endpoint	Test Duration (hr)	Species	Value	Source
	NOEC(ECx)	720	Algae or other aquatic plants	0.001mg/L	4
	BCF	1680	Fish	58-116	7
	LC50	96	Fish	0.012-0.019mg/L	4
	EC50	48	Crustacea	0.56mg/L	5
	EC50	72	Algae or other aquatic plants	0.011mg/L	4
	EC50	96	Algae or other aquatic plants	0.68-2.9mg/l	4

water	Endpoint	Test Duration (hr)	Species	Value	Source
	Not Available	Not Available	Not Available	Not Available	Not Available

**Ecotoxicity:**

The tolerance of water organisms towards pH margin and variation is diverse. Recommended pH values for test species listed in OECD guidelines are between 6.0 and almost 9. Acute testing with fish showed 96h-LC50 at about pH 3.5

for petroleum waxes:

**Environmental fate:**

Most hydrocarbon components of substances in this Group will have little or no tendency to partition to air. The half lives for degradation of these hydrocarbons by reaction with hydroxyl radicals, in the troposphere, under the influence of sunlight, will all be less than one day, by extrapolation from the data quoted by Atkinson. Accordingly, any hydrocarbon material which does partition to air will be rapidly photodegraded

As hydrocarbon number increases above C13, as is the case for the majority of the wax constituents, Log K values >6 are predicted. Substances having Log K estimates greater than 6 are characterised by extremely large molecular weight and subsequent hydrophobicity, therefore no significant aqueous exposures or bioaccumulation are expected to occur.

Since molecular weight and structural conformation determines in large part the solubility and vapour pressure characteristics of the hydrocarbons, modeling focused on the lower molecular weight hydrocarbons. These would be selected C13 and C20 hydrocarbons since waxes consist mostly of C20 to C85 compounds, with some minimal percent of C13 through C20 hydrocarbons. Therefore, the majority of the physicochemical modeling was performed on various paraffinic, naphthenic and aromatic representatives containing 13 and C20 carbon atoms.

log Kow ranged from 4.7 >6.7

**Water solubility:** The water solubility of waxes cannot be determined due to their complex mixture characteristics. The highest solubilities would be exhibited by only a small fraction of the hydrocarbon molecules present in waxes. Increasing carbon number results in rapidly decreasing solubility, so that the most-soluble (predominantly methyl-substituted diaromatic) C18 and C20 analogues yield model values of 0.01195 and 0.00125 mg/l, respectively. Higher molecular weight (higher carbon number) components are even less water soluble. Based on water solubility modeling for C13 components of complex mixtures, aqueous solubilities of these waxes are typically much less than 1 ppm, due to differential partitioning of components between the aqueous and organic phases.

**Hydrolysis:** Materials in the waxes category are not subject to hydrolysis, as they lack these reactive groups with which a water molecule or hydroxide ion reacts to form a new carbon-oxygen bond.

**Photodegradation:** Although waxes typically have low vapour pressures, volatilisation of some lower molecular weight components exhibit relatively high atmospheric oxidation half-lives. Therefore, those compounds that may partition to the atmosphere will be removed through indirect photochemical degradation. All modeled components exhibited rapid degradation in the atmosphere; the value presented represents both the most volatile component and the longest modeled half-life. All other modeled C13 components had both lower volatility and shorter half-lives.

**Result :** t1/2 = 0.913 days (10.96 hr) for most volatile C13 component modeled

**Transport between Environmental Compartments:** Fugacity-based computer modeling indicated that the majority of high molecular weight hydrocarbons with carbon numbers of C20 and greater in waxes would be distributed to soil. Percent distribution estimates were modeled with C13 to C29 branched paraffins as this class of wax hydrocarbons shows the greater distribution to air. Aromatic compounds with carbon numbers from C13 through C85 will partition principally to soil. Linear paraffins and naphthenes distribute to both soil and air, with increasing partitioning to soil for hydrocarbons greater than C20 as vapour pressure decreases. Since the majority of hydrocarbon components in waxes are primarily normal paraffins of C20. and greater, with moderate to minimal amounts of naphthenics, isoparaffins and trace amounts of aromatics, volatility is not a significant fate process for these petroleum substances due to negligible vapor pressures at ambient

Continued...

## Burnley Korean

temperatures and their high molecular weight. As hydrocarbon number increases above C20, partitioning to soil is the predominant behavior of these compounds.

**Biodegradation:** Not readily biodegradable; inherently biodegradable and extensively biodegradable in long-term exposures. Waxed paper decomposes at about the same rate as unwaxed paper. Soil invertebrates contribute significantly to the decomposition of waxed paper in leaf litter. Decomposition of waxed paper occurs more rapidly during the autumn/winter, when there is a fresh layer of leaf litter on the ground, than during the spring/summer, when the last autumn's leaf litter has been largely reduced to humus

Degradation (28 days): 21% OECD 301B

**Ecotoxicity:**

Fish LC50 (96 h): Oncorhynchus mykiss >6000 mg/l (hydrotreated heavy paraffinic distillate); >1000 mg/l (solvent refined heavy paraffinic distillate); >10000 mg/l (white mineral oil)

Daphnia magna EC50: (48 h): >10000 mg/l (solvent refined heavy paraffinic distillate) (immobilisation)

Algae EC50 (96 h): Scenedesmus subspicatus >1000 mg/l (solvent refined residual oil) (growth rate, biomass)

It has been confirmed experimentally that for fish and invertebrates, paraffinic hydrocarbons with a carbon number of 10 or higher (log Kow >5) show no acute toxicity and that alkylbenzenes with a carbon number of 14 or greater (log Kow >5) similarly show no acute toxicity. From these well-demonstrated solubility 'cut-offs' for acute toxicity of hydrocarbon substances, which directly relate to their physico-chemical properties, it is clear that the same should hold for complex petroleum substances.

Paraffinic hydrocarbons with carbon numbers of greater than 14 (log Kow >7.3) should show no measurable chronic toxicity. The existence of this cut-off for chronic toxicity is supported for petroleum substances by the numerous chronic toxicity studies reported on lubricant base oils, which demonstrate that for these substances which are composed primarily of alkanes and naphthenes of C15 and greater, no evidence of chronic toxicity is seen.

Drinking Water Standards: hydrocarbon total: 10 ug/l (UK max.).

For Zinc and its Compounds: BCF: 4 to 24,000.

Environmental Fate: Zinc is capable of forming complexes with a variety of organic and inorganic groups and is an essential nutrient present in all organisms.

Atmospheric Fate: Zinc concentrations in the air are relatively low, except near industrial sources, such as smelters. There is no estimate for the atmospheric lifetime of zinc, but, since zinc is transported long distances in air, its lifetime in air is at least on the order of days. Zinc is removed from the air by dry/wet deposition.

Terrestrial Fate: Soil Zinc may magnify in the soil if concentrations of the substance exceed 1632 ppm. The relative mobility of zinc in soil is determined by the same factors that affect its transport in aquatic systems, (i.e. solubility of the compound, pH, and salinity). The mobility of zinc in soil increases at lower soil pH, under oxidizing conditions, and at lower cation, (positive ion), exchange capacities. However, the amount of zinc in solution generally increases @ pH >7, in soils high in organic matter. Clay and metal oxides sorb zinc and tend to retard its mobility in soil. Zinc is more mobile at pH 4 than at pH 6.5 as a consequence of sorption. Under low oxygen conditions, zinc sulfide is the controlling species, which has low mobility. Plants - Zinc is not expected to concentrate in plants, however, this depends on plant species, soil pH, and soil composition.

Aquatic Fate: Zinc readily adsorbs to sediment and suspended particles. The substance can persist in water indefinitely and can be toxic to aquatic life. Hydrous iron, manganese oxides, clay minerals, and organic material may help remove zinc from sediment since they adsorb the substance. Environmental toxicity of zinc in water is dependent upon the concentration of other minerals and the pH of the solution. Zinc remains as the free ion at lower pH levels. At high pH levels, zinc in solution is precipitated as zinc hydroxide, zinc carbonate, or calcium zincate.

Ecotoxicity: Zinc concentrates moderately in aquatic organisms; concentration is higher in crustaceans and bivalve species than in fish. Zinc is not expected to magnify as it moves up the land-based food chain. Zinc can concentrate over 200,000 times in oysters. Copper can increase toxicity to fish and calcium can decrease toxicity. Zinc can accumulate in freshwater species at 5 -1,130 times the concentration present in the water. Crustaceans and fish accumulate zinc from water and food. The substance has been found in very high concentration in aquatic invertebrates. Sediment dwelling organisms have higher zinc concentrations than those living in the aqueous layer. Overexposures to zinc also have been associated with toxic effects in mammals, including man. Ingestion of zinc or zinc-containing compounds has resulted in a variety of effects in the gastrointestinal tract and blood in humans and animals. The substance may cause lesions in the liver, pancreas, and kidneys.

Prevent, by any means available, spillage from entering drains or water courses.

**DO NOT** discharge into sewer or waterways.

### Persistence and degradability

Ingredient	Persistence: Water/Soil	Persistence: Air
zinc chloride	HIGH	HIGH

### Bioaccumulative potential

Ingredient	Bioaccumulation
zinc chloride	HIGH (BCF = 16000)

### Mobility in soil

Ingredient	Mobility
zinc chloride	LOW (KOC = 23.74)

## SECTION 13 Disposal considerations

### Waste treatment methods

<b>Product / Packaging disposal</b>	<ul style="list-style-type: none"> <li>▸ Containers may still present a chemical hazard/ danger when empty.</li> <li>▸ Return to supplier for reuse/ recycling if possible.</li> </ul> <p>Otherwise:</p> <ul style="list-style-type: none"> <li>▸ If container can not be cleaned sufficiently well to ensure that residuals do not remain or if the container cannot be used to</li> </ul>
-------------------------------------	---


Continued...

## Burnley Korean

	<p>store the same product, then puncture containers, to prevent re-use, and bury at an authorised landfill.</p> <ul style="list-style-type: none"> <li>▶ Where possible retain label warnings and SDS and observe all notices pertaining to the product.</li> </ul> <p>Recycle wherever possible.</p> <ul style="list-style-type: none"> <li>▶ Consult manufacturer for recycling options or consult local or regional waste management authority for disposal if no suitable treatment or disposal facility can be identified.</li> <li>▶ Treat and neutralise at an approved treatment plant. Treatment should involve: Mixing or slurring in water; Neutralisation with soda-lime or soda-ash followed by: burial in a land-fill specifically licensed to accept chemical and / or pharmaceutical wastes or Incineration in a licensed apparatus (after admixture with suitable combustible material)</li> <li>▶ Decontaminate empty containers with 5% aqueous sodium hydroxide or soda ash, followed by water. Observe all label safeguards until containers are cleaned and destroyed.</li> </ul>
--	---

## SECTION 14 Transport information

## Labels Required

	
Marine Pollutant	NO

## Land transport (TDG)

UN number	1759	
UN proper shipping name	CORROSIVE SOLID, N.O.S. (contains zinc chloride)	
Transport hazard class(es)	Class	8
	Subrisk	Not Applicable
Packing group	III	
Environmental hazard	Not Applicable	
Special precautions for user	Special provisions	16
	Explosive Limit and Limited Quantity Index	5 kg
	ERAP Index	Not Applicable

## Air transport (ICAO-IATA / DGR)

UN number	1759	
UN proper shipping name	Corrosive solid, n.o.s. * (contains zinc chloride)	
Transport hazard class(es)	ICAO/IATA Class	8
	ICAO / IATA Subrisk	Not Applicable
	ERG Code	8L
Packing group	III	
Environmental hazard	Not Applicable	
Special precautions for user	Special provisions	A3 A803
	Cargo Only Packing Instructions	864
	Cargo Only Maximum Qty / Pack	100 kg
	Passenger and Cargo Packing Instructions	860
	Passenger and Cargo Maximum Qty / Pack	25 kg
	Passenger and Cargo Limited Quantity Packing Instructions	Y845
	Passenger and Cargo Limited Maximum Qty / Pack	5 kg

## Sea transport (IMDG-Code / GGVSee)

UN number	1759
UN proper shipping name	CORROSIVE SOLID, N.O.S. (contains zinc chloride)

## Burnley Korean

Transport hazard class(es)	IMDG Class	8
	IMDG Subrisk	Not Applicable
Packing group	III	
Environmental hazard	Not Applicable	
Special precautions for user	EMS Number	F-A , S-B
	Special provisions	223 274
	Limited Quantities	5 kg

## Transport in bulk according to Annex II of MARPOL and the IBC code

Not Applicable

## Transport in bulk in accordance with MARPOL Annex V and the IMSBC Code

Product name	Group
petrolatum	Not Available
zinc chloride	Not Available

## Transport in bulk in accordance with the ICG Code

Product name	Ship Type
petrolatum	Not Available
zinc chloride	Not Available

## SECTION 15 Regulatory information

## Safety, health and environmental regulations / legislation specific for the substance or mixture

This product has been classified in accordance with the hazard criteria of the Hazardous Products Regulations and the SDS contains all the information required by the Hazardous Products Regulations.

## petrolatum is found on the following regulatory lists

Canada Categorization decisions for all DSL substances

Canada Domestic Substances List (DSL)

Canada Toxicological Index Service - Workplace Hazardous Materials

Information System - WHMIS GHS

Chemical Footprint Project - Chemicals of High Concern List

International Agency for Research on Cancer (IARC) - Agents Classified by the IARC Monographs

International Agency for Research on Cancer (IARC) - Agents Classified by the IARC Monographs - Group 1: Carcinogenic to humans

## zinc chloride is found on the following regulatory lists

Canada Categorization decisions for all DSL substances

Canada Domestic Substances List (DSL)

## National Inventory Status

National Inventory	Status
Canada - DSL	Yes
Canada - NDSL	No (petrolatum; zinc chloride)
USA - TSCA	Yes
<b>Legend:</b>	Yes = All CAS declared ingredients are on the inventory No = One or more of the CAS listed ingredients are not on the inventory and are not exempt from listing (see specific ingredients in brackets)

## SECTION 16 Other information

Revision Date	04/05/2021
Initial Date	03/15/2021

## SDS Version Summary

Version	Issue Date	Sections Updated
0.2.1.1.1	04/04/2021	Advice to Doctor, Classification, Environmental, Fire Fighter (fire/explosion hazard), Ingredients, Physical

Continued...

## Burnley Korean

Version	Issue Date	Sections Updated
		Properties

### Other information

The SDS is a Hazard Communication tool and should be used to assist in the Risk Assessment. Many factors determine whether the reported Hazards are Risks in the workplace or other settings. Risks may be determined by reference to Exposures Scenarios. Scale of use, frequency of use and current or available engineering controls must be considered.

### Definitions and abbreviations

PC—TWA: Permissible Concentration-Time Weighted Average PC  
 –STEL: Permissible Concentration-Short Term Exposure Limit  
 IARC: International Agency for Research on Cancer  
 ACGIH: American Conference of Governmental Industrial Hygienists  
 STEL: Short Term Exposure Limit  
 TEEL: Temporary Emergency Exposure Limit.  
 IDLH: Immediately Dangerous to Life or Health Concentrations  
 ES: Exposure Standard  
 OSF: Odour Safety Factor  
 NOAEL :No Observed Adverse Effect Level  
 LOAEL: Lowest Observed Adverse Effect Level  
 TLV: Threshold Limit Value  
 LOD: Limit Of Detection  
 OTV: Odour Threshold Value  
 BCF: BioConcentration Factors  
 BEI: Biological Exposure Index  
 AIIC: Australian Inventory of Industrial Chemicals  
 DSL: Domestic Substances List  
 NDSL: Non-Domestic Substances List  
 IECSC: Inventory of Existing Chemical Substance in China  
 EINECS: European INventory of Existing Commercial chemical Substances  
 ELINCS: European List of Notified Chemical Substances  
 NLP: No-Longer Polymers  
 ENCS: Existing and New Chemical Substances Inventory  
 KECI: Korea Existing Chemicals Inventory  
 NZIoC: New Zealand Inventory of Chemicals  
 PICCS: Philippine Inventory of Chemicals and Chemical Substances  
 TSCA: Toxic Substances Control Act  
 TCSI: Taiwan Chemical Substance Inventory  
 INSQ: Inventario Nacional de Sustancias Químicas  
 NCI: National Chemical Inventory  
 FBEPH: Russian Register of Potentially Hazardous Chemical and Biological Substances